

MM300 OEM Moisture Transducers



For integrated, cost effective moisture analysis for OEM's and multiple sampling points



Wall Mounted Sample System (optional)



MM300 Moisture Sensor



Monitor (optional)

Applications

Glove Boxes
Gas Shrouding

Inert Enclosures
Room Monitoring

Nitrogen Generators
HVAC

Features & Benefits

- IP66 (NEMA 4) Protection
- Measurement range -100 to +20°C Dew Point
- Fast response
- Temperature compensated over operating temperature range
- 2 wire loop powered
- Optional easy to read monitor with bright LED displays eliminate reading errors
- Optional remote monitoring
- Optional Intrinsically Safe transducer
- Optional wall mounted Sample System
- Calibration traceable to NIST

Conforms to European Directives:

Electromagnetic Compatibility Directive 89/336/EEC Low Voltage Directive 73/23/EEC

When simple, accurate moisture measurement is required, the MM300 is the ideal choice.


Designed with the OEM user in mind, the MM300 transducer and monitor can be easily integrated into a wide range of systems. This 2 wire loop powered dew point transmitter is designed for moisture measurement in gases. Suitable for applications in the petrochemical, power generation and process industries. The 4-20mA output measures dew point

temperature in gases at line pressure or atmospheric pressure.

The MM300 mounts directly in the gas stream for applications including glove boxes, environmental chambers and test chambers.

The optional monitors provide many additional functions including alarm set points and 4-20mA re-transmission and provides the power for the current loop.

MM300 Dimensions (mm)



Technical Specifications

Measurement Ranges	-100°C to +20°C (-148°F to +68°F) Dew Point
Accuracy	±2°C (±3.6°F) Dew Point
Response time	90% of reading (T95) less than 5 minutes (dry to wet)
Signal outputs	4-20mA (2 wire)
Operating Conditions	
Operating Humidity	0-100% RH
Operating Temperature	-40°C to +60°C (-40°F to +140°F)
Operating Pressure	450 Barg / 6500 psi / 45 mPa
Flow Rate	0.5 to 7 NL/min
Power Requirements	12 to 28 VDC
Load Resistance	Max 250 Ω @ 12 VDC Max 500 Ω @ 24 VDC

Systech Illinois have over 30 years experience of providing analysis solutions for a wide range of industries. From our manufacturing plants in the UK and U.S we produce gas analysers for industrial process industries, headspace analysers for monitoring gas flushing of food products, and our range of permeation analysers.

Systech Instruments Ltd (UK)
17 Thame Park Business Centre,
Wenman Road,
Thame, Oxfordshire OX9 3XA
Tel: +44 (0)1844 216838
Fax: +44 (0)1844 217220
E-mail: sales.uk@systechillinois.com
www.systechillinois.com

Illinois Instruments, Inc (U.S)
2401 Hiller Ridge Road
Johnsburg, Illinois 60051
U.S.A
Tel: +1 815 344 6212
Fax: +1 815 344 6332
E-mail: sales.usa@systechillinois.com
www.systechillinois.com

Illinois Instruments (Thailand)
26/6 Ladprao 23, Jatujak,
Bangkok 10900
Thailand
Tel: +66 (0)2030 5851
Fax: +66 (0)2030 5850
E-mail: sales.ap@systechillinois.com
www.systechillinois.com

Systech Illinois (China)
Room 1107-1108 Forte Building
No. 910 Quyang Rd, Hongkou district,
Shanghai, China 200437
Tel: +86 21 65533022
Fax: +86 21 65539651
E-mail: info@systechillinois.cn
www.systechillinois.cn